3M™ Digital Projector WX36

The WX36 projector offers a perfect balance of size, weight, brightness and compatibility. At only 3.6kg, 3000 lumens, and WXGA resolution, this projector is an excellent choice for a modern conference room or classroom and is compatible with wide aspect ratio PCs notebooks and video conferencing devices. It offers full connectivity including HDMI and is HDTV compatible. It is virtually a maintenance-free multipurpose data projector offering great performance and low cost of ownership. The WX36 also features extended hybrid filter life with 4000 hour cleaning cycles.

3M WX36 Projector
78-9236-7720-3

Features

- 3000 lumens*
- 2000:1 contrast ratio
- AutoVertical Keystone Adjustment
- Quick Start and Instant Off
- Network Contol, Management and Presenting
- 16W Audio Out sound
- HDMI connectivity
- USB Display
- AMX Device Discovery
- Advanced Security Features
- Light weight: 3.6kg

**Indicates maximum lumens rating*



Optical

Resolution
Native: WXGA (1280 x 800)
Maximum: UXGA (1600 x 1200)

Imager set
0.59", P-Si TFT Panel x3

Aspect Ratio
16:10 native and 4:3, 16:9, 14:9 letterbox

Colors
16.7 million true colors (24 bit)

Contrast Ratio
2000:1

Brightness
3000 lumens (maximum), 2200 lumens (eco mode)

Projection Lens
F1.67-1.91 (f=19-23mm

Vertical Lens Shift
9:1 Fixed

Screen Size (range)
30-300 inches

Zoom/Focus
Manual

Zoom Ratio
1.2:1

Throw Ratio (distance:width)
1.5:1 - 1.8:1

Optional Lenses
NA

Lamp
UHB 210W (normal mode), 140W (eco mode)

Lamp Life*
Up to 3000 hours (normal mode)
Up to 6000 hours (eco mode)
** Lamp life may vary due to environment and usage. Lamp brightness decreases over time.*

Size

Dimensions (W x H x D)
12.5 x 3.9 x 11.3 in. (317 x 98 x 288mm)

Weight
3.6kg

Warranties

Projector
3 years or 2500 hours

Lamp
90 days or 180 hours

System Specifications

Video Compatibility
NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM

SDTV/HDTV
525i (480i), 525p (480p), 625i (576i)/ 750p (720p@60Hz), 1125i (1080i@60Hz)

Digital Keystone Correction
Vertical ±30 degrees

Mouse Emulation
USB

Audio
1 x 16 Watt

Startup Screen
Customizable

Noise Level
Normal 37dB; Eco 30dB

Feature Set
Auto off, 4x digital magnification, image blank

Horizontal Scan
31.5 - 106 kHz

Vertical Scan
56 - 120 Hz

Power Consumption
330W (Eco Stand-by) less than 1 watt

Power Supply
AC 110~120V /220~240V (50/60 Hz)

Regulatory Approvals
UL, cUL, FCC Part 15 Subpart B, Class B, EN60950-1, CE

Operating Temperature
41°- 95°F (5°- 35°C)

Storage Temperature
-4°- 140°F (-20°- 60°C)

Altitude
Sea level to 6000 ft. (1,829m)

Technical Support

• Free unlimited software downloads and updates available on our website at www.3m.com/meetings

Connections

Computer
Computer 1,2 15 pin HD-Sub – Analog Computer Input
USB Type B – Mouse Emulation
Monitor Out 15 Pin HD-Sub – Analog Computer Output
USB Type A – PC-Less Presentations
Control 9 Pin D-Sub – RS-232 Control Port
Audio in 1, 2 3.5mm Stereo mini jack – PC Audio input

Video
HDMI – Digital Video and Audio
Component 3xRCA (Y, Cb/Pb, Cr/Pr) – Component Video input
S-Video 4 Pin Mini-Din – S-Video Input
Video RCA – Composite Video Input
Audio In 3, 2xRCA (red, white) – Right and Left Channel Input
Audio Out, 2xRCA (red, white) – Right and Left Channel Output
MIC 3.5mm stereo – Microphone Audio Input

Wired LAN
Standard: 10 BASE-T / 100 BASE-TX
Connection: RJ-45
Featuring:
PJCtrl: Control a projector via the network
PJImg: Create MyImage file and send it to the projector
PJMan: Control multiple projectors via the network
PJMessenger: Transmit and display a message on a projector via the network
Liveviewer: Wireless presentations via the Lan

Accessories Included

Network Contol, Management and Presenting Software
Power cords (US, UK, Europe)
Remote control without laser (with AA batteries)
RGB cable
Multi-Language Operator's Guide CD
Lens cap

Optional Accessories

Lamp replacement kit	78-6972-0008-3
Universal ceiling mount	78-6969-9874-5
Adjustable height extension	78-6969-9698-8

Screen Size Diagonal [inch (m)]	Image Size 16:10 Projection Distance Min. [inch (m)]	Image Size 16:10 Projection Distance Max. [inch (m)]	Image Size 4:3 Projection Distance Min. [inch (m)]	Image Size 4:3 Projection Distance Max. [inch (m)]
30" (0.8)	36" (0.9)	44" (1.1)	41" (1.1)	50" (1.3)
60" (1.5)	74" (1.9)	89" (2.3)	84" (2.1)	101" (2.6)
80" (2.0)	99" (2.5)	119" (3.0)	112" (2.8)	135" (3.4)
100" (2.5)	124" (3.1)	149" (3.8)	140" (3.6)	169" (4.3)
150" (3.8)	186" (4.7)	224" (5.7)	211" (5.4)	254" (6.4)
200" (5.1)	6.3" (249)	299" (7.6)	282" (7.2)	338" (8.6)
300" (7.6)	374" (9.5)	449" (11.4)	423" (10.7)	508" (12.9)

Note: These sizes are +10 percent. This is due to variations in the manufacture of the lens. If you are close to one of the endpoints you should verify with your unit that the image is the proper size at the proper distance.

PJLink™

Trademark PJLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas.

www.3m.com/meetings

3M

Projection Systems
3M Centre
Cain Road, Bracknell
Berkshire RG12 8HT

Tel: +44 (0)1234 229695
Email: pjappy1@mmm.com

Projection Systems
Dubai Internet City
Bldg. 11, 3rd Floor
P.O. Box 20191

Tel: +9714 3670 777
Email: projectors.gulf@mmm.com
Fax: +9714 3670 663

© 3M 2011. All rights reserved. Please recycle. v01.11

Important Notice
All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M. Specifications subject to change without notice.

Warranty; Limited Remedy; Limited Liability
This product will be free from defects in material and manufacture for a period of 3 years or 2500 hours from the time of purchase. 3M MAKES NO OTHER WARRANTIES or CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M, and the 3M logo are trademarks of 3M Company. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.